



ALL PLYWOOD IS EXTERIOR-TYPE (EXT-D) PAIR
ROOF AND ROOF DOOR PLYWOOD IS 1/2" THICK
ALL OTHER PLYWOOD IS 3/4" THICK.

ALL FASTENERS SHOULD BE CORROSION RESISTANT OR STAINLESS STEEL

NAILS - USE 8D NAILS 6" O.C. WHEN NAILING PLYWOOD TO SUPPORTS, ON ENDS OF BINS, 16d @ 6" O.C. (BULKHEADS BULKHEADS ARE TIED TOGETHER WITH 1/2"

THE BIN MAY BE USED ON ANY SUPPORT SYSTEMS SUCH AS PIER FOOTINGS, WELL BRACED LEGS OR LOW WALLS WITH FOOTINGS.

EACH OF THE COMPARTMENTS HOLDS 5 TONS OF
60 PCF FERTILIZER

THIS SHEET SHOWS A THREE COMPARTMENT BIN FOR BINS WITH MORE OR LESS, THE LENGTHS OF SKIDS AND SIDE MEMBERS SHOULD BE ADJUSTED.



**BIN FLOOR DETAIL
CLOSED SIDE**



**BIN FLOOR DETAIL
DOOR OPENING SIDE**

DESIGNED:
AMERICAN PLYWOOD ASSOCIATION
TACOMA, WASHINGTON

COOPERATIVE EXTENSION WORK IN

AGRICULTURE AND HOME ECONOMICS

DEPARTMENT OF AGRICULTURAL ENGINEERING

UNIVERSITY OF MARYLAND
AIR

AND
UNITED STATES DEPARTMENT OF AGRICULTURE COOPERATING

TRANSPORTABLE STORAGE BIN

FOR FERTILIZER IN BULK

APA '69 6072 SHEET 1 OF 3

1000 JOURNAL OF POST KEYNESIAN ECONOMICS